

Appl. Serial No. 10/698,395
Amendment Dated August 6, 2009
Reply to Office Action Mailed May 6, 2009

RECEIVED
CENTRAL FAX CENTER

AUG 06 2009

AMENDMENTS TO THE CLAIMS

This listing of claims replaces all prior versions, and listings, of claims in the application:

- 1 1. (Currently Amended) ~~An antenna~~ A system for a transmitter comprising:
2 a plurality of antennas ~~defining to define~~ a respective plurality of fixed beams which
3 together cover a coverage area;
4 for each antenna, a respective signal generator ~~generating to generate~~ a respective signal
5 comprising a common overhead component common to all the signals, using a spreading code
6 common to all signal generators;
7 transceiver circuitry connecting the signal generators to the antennas such that a
8 respective one of the signals is transmitted by each antenna, the signals ~~being to be~~ transmitted
9 substantially simultaneously;
10 for each pair of said antennas having overlapping beams within said coverage area, the
11 respective signal generators ~~using to use~~ the spreading code with a mutual micro-timing offset
12 that is large enough that destructive cancellation substantially does not occur between the
13 common overhead components transmitted on the overlapping beams ~~pair of antennas~~.
- 1 2. (Currently Amended) ~~An antenna~~ A system according to claim 1, implemented for a plurality
2 of coverage areas, each coverage area being a respective sector served by ~~[[the]]~~ a base station,
3 wherein the plurality of fixed beams together cover a corresponding one of the sectors.
- 1 3. (Original) A system according to claim 1 wherein the transmitter is a CDMA base station, and
2 each signal is a CDMA signal.
- 1 4. (Original) A system according to claim 2 wherein the transmitter is a CDMA base station, and
2 each signal is a CDMA signal.
- 1 5. (Previously Presented) A system according to claim 1, wherein the coverage area is a cell
2 sector, wherein the respective mutual micro-timing offset is less than a predefined maximum
3 value such that the mutual micro-timing offset does not cause a source of one of the signals to be
4 incorrectly identified as located in another cell sector.

Appln. Serial No. 10/698,395
Amendment Dated August 6, 2009
Reply to Office Action Mailed May 6, 2009

1 6. (Currently Amended) A system according to claim [[4]]5 wherein:
2 the sector has a sector-specific spreading code, and wherein the respective mutual micro-
3 timing offset between each pair of ~~CDMA~~-signals is realized by applying the sector-specific
4 spreading code with a respective mutual micro-timing offset.

1 7. (Original) A system according to claim 6 wherein the sector-specific spreading code is a PN
2 code.

1 8. (Previously Presented) A system according to claim 7 wherein each mutual micro-timing
2 offset is at least one chip and less than eight chips.

1 9. (Currently Amended) A system according to claim 7 wherein each mutual micro-timing offset
2 is less than half a width of a traffic search ~~less than a window/space window~~ implemented in a
3 mobile terminal ~~community communicating~~ with the ~~base station~~transmitter.

1 10. (Currently Amended) A system according to claim 6 wherein the sector-specific spreading
2 code is a short code having a sector specific offset used to distinguish between other sources
3 using the same short code, and wherein the respective mutual micro-timing offset is small
4 enough that substantially no ambiguity between different sector specific offsets occurs at a
5 receiver in respect of any pair of signals transmitted by adjacent antennas.

1 11. (Original) A system according to claim 10 wherein the short code is of length $2^{15}-1$.

1 12. (Original) A system according to claim 4 wherein: the sector has a sector-specific spreading
2 code, and wherein the respective mutual micro-timing offset between each pair of CDMA signals
3 is realized by applying the sector-specific spreading code and then applying a mutual micro-
4 timing offset.

Appln. Serial No. 10/698,395
Amendment Dated August 6, 2009
Reply to Office Action Mailed May 6, 2009

1 13. (Original) A system according to claim 4 wherein:
2 the sector has a sector-specific spreading code, and wherein the respective mutual micro-
3 timing offset between each pair of CDMA signals is realized by applying the micro-timing offset
4 to respective sector-specific spreading code generators.

1 14. (Original) A system according to claim 12 wherein the sector-specific spreading code is a PN
2 code.

1 15. (Currently Amended) A system according to claim [[4]]1 wherein the common overhead
2 component comprises at least one of pilot channel, sync channel, paging channel, quick paging,
3 advanced access channel and auxiliary pilot.

1 16. (Original) A system according to claim 4 further comprising:
2 for each active user located within the sector, at a given instant only one of the CDMA
3 signals includes a user-specific traffic component generated by the respective CDMA signal
4 generator.

1 17. (Previously Presented) A system according to claim 16 wherein the one of the CDMA
2 signals to include the user-specific traffic component for a given user is identified by analyzing
3 signal strength on reverse links from the user, and selecting the CDMA signal corresponding
4 with the reverse link having a best signal strength.

1 18. (Original) A system according to claim 1 wherein the transceiver circuitry is further adapted
2 to provide transmit frequencies in a manner such that the transmit frequencies include a
3 frequency offset from one another.

1 19. (Currently Amended) A system according to claim 18 comprising a beam-forming matrix
2 connected to the plurality of antennas.

Appl. Serial No. 10/698,395
Amendment Dated August 6, 2009
Reply to Office Action Mailed May 6, 2009

- 1 20. (Original) A system according to claim 19 wherein the beam-forming matrix is a Butler
2 matrix.
- 1 21. (Currently Amended) A system ~~[[of]]~~according to claim 18 wherein the frequency offset is
2 chosen to further reduce undesirable effects of signal cancellation.
- 1 22. (Original) A system according to claim 18 wherein the signals have unique traffic channels.
- 1 23. (Previously Presented) A system according to claim 22 wherein the frequency offset is a
2 multiple other than that of a frame rate.
- 1 24. (Original) A system according to claim 18 wherein the frequency offset is greater than 30 Hz
2 and less than 120 Hz.
- 1 25. (Original) A system according to claim 1 further comprising:
2 means in the ~~transceivers~~ transceiver circuitry for providing transmit phases that include a
3 time dependent phase offset from one another, wherein the phase offset is chosen to reduce
4 undesirable effects of signal cancellation.
- 1 26. (Currently Amended) A method in a ~~CDMA~~an antenna system comprising:
2 transmitting, from antennas of the antenna system, signals each having a common
3 overhead component on a plurality of beams within a sector, with a micro-timing offset of a
4 spreading code used by the signals transmitted on adjacent overlapping beams, wherein the
5 micro-timing offset is large enough that destructive cancellation substantially does not occur
6 between common overhead components on the adjacent overlapping beams,
7 wherein the plurality of beams are transmitted in the sector that is from among plural
8 sectors of a cell.
- 1 27. (Currently Amended) A method according to claim 26 wherein the sector has a sector-
2 specific spreading code, and wherein the respective micro-timing offset between each pair of

Appln. Serial No. 10/698,395
Amendment Dated August 6, 2009
Reply to Office Action Mailed May 6, 2009

3 CDMA-signals is realized by applying the sector-specific spreading code with a respective
4 mutual micro-timing offset.

1 28. (Previously Presented) A system according to claim 1, wherein the plurality of fixed beams
2 defined by the corresponding plurality of antennas together cover a sector from among plural
3 sectors of a cell.

1 29. (Previously Presented) A method according to claim 26, wherein the micro-timing offset is
2 less than a predefined maximum value such that the micro-timing offset does not cause a source
3 of one of the signals to be incorrectly identified as located in another sector.